

JT-A7

CLEAR AUDIO COPY FREQUENCY SHORTCUT

Monitor/Square function ■



Scan / VOX ■



(TOT) Time out timer ■



(BCL) Busy channel lockout ■



Battery save ■



Low battery alarm /
Channel announcement ■



Main Function

- Monitor/Square function
- Scan
- (VOX)
- (TOT) Time out timer
- (BCL) Busy channel lockout
- Battery save
- Low battery alarm
- Channel announcement

Basic parameters

	BRIEF PARAMETER
Frequency range	400-450MHz
Operating temperature range	-20°C~50°C
Channel capacity	16channels
Communication system	Simplex or Double frequency simplex
Weight	268g(including battery pack)
Battery capacity	1600mAh
Output power	2watts
Modulation Type	FM(F3E)
Frequency deviation	≤±5KHz
Spurious Emission	≤-60dB
TX current	≤1.5A
Frequency stability	±2.5ppm
RX sensitivity	<0.18μV
Audio sensitivity	≥400mW
Standby current	72mA(36 mA Power save condition:36mA)
Dimension	101(L)X52(W)X35(D)mm

Standard Accessories



Radio device*1



Belt clip*1



Antenna*1



Battery*1



Adaptor & cable*1



Lanyard*1

Authorized distributor

