

WETALK
Powered By LJE



Waterproof IP67



Vibration



Noise cancelling



T-800D

Frequency 400-480MHz

- Output power 5W/0.5W
- PTT ID, ANI
- Memory Channel 199
- Remote Kill , Stun, Activate & Revive
- Record function
- 2 Tone & 5 tone signaling 1750Hz
- Scrambler
- Compander
- VOX function
- Waterproof IP67
- Vibration
- Noise cancelling

WETALK
Powered By LJE

T-800D

Frequency 400-480MHz



Waterproof IP67



Vibration



Noise cancelling



General	
Frequency Range	400-480MHz
Antenna	High Gain Antenna
Frequency Stability	±2.5ppm
Memory Channel	199 Channels
Working voltage	DC 7.4V
Antenna Impedance	50Ω
Operating Mode	simplex or co-frequency or alien
Dimensions	116*61*38mm
Li-ion Battery Capacity	2000MAH

Packing list	
Antenna	Li-ion Battery
Adaptor	Charger
Sling	

Transmit part	
RF power	5W
Modulate Mode	F3E
Max.Freq.Deviation	≤5KHz
Remain Wave Radiation	≤60db
Transmitting Current	≤1000mah
Receiver part	
Sensitivity	<0.20uV (12dB SINAD)
Squelch Sensitivity	<0.20uV
Intermodulation Antijamming	50db
Audio Power output	500mW
Receiving Current	≤100mh
Squelch Stangby	20ma

LJE Communications Sdn Bhd.

